










		Chamber Combined Vibration Test System	Chamber Combined Vibration Test System with a Slip Table	Chamber Combined Vibration Test System with a Slip Table		
Model		i220/SA1M	i240/SA3M	A74/EM8HAG	EM2401	EM2555
image						
Features		For low cost environmental test IEC60068-2-6, 27, 64 compliant For high frequency test	IEC60068-2-6, 27, 64 compliant ISO19453 compliant	用于大负荷电阻测试 符合IEC60068-2-6、 27、64标准 符合ISO19453标准	IEC60068-2-6, 27, 64 compliant ISO19453 compliant Horizontal / vertical excitation changeover type	IEC60068-2-6, 27, 64 compliant ISO19453 compliant Horizontal / vertical excitation changeover large type
Frequency Range (to Hz)		3300	2600	至2600	2600	2600
Rated Force	Sine (kN)	8	24	74	24	49
	Random (kN rms)	8	24	74	24	49
	Shock (kN)	16	48	180	48	98
Maximum Acc. (m/s ²)		1159	1200	973	1142	753
Maximum Vel. (m/s)		2.2	2.2	2	2.2	2.4
Maximum Displacement (mmp-p)		51	51	76.2	51	100
Maximum Load (kg)		200	400 (Horizontal)/ 400 (Vertical)	1,000	400 (Horizontal)/ 300 (Vertical)	1000 (Horizontal)/ 500 (Vertical)
Slip Table W×D (mm)		-	800 × 800	950 × 1100	630 × 630	1000 × 1000
Chamber	Internal Dimensions W×D×H (mm)	1000 × 1000 × 1000	-	1200 × 1200 × 1200	1000 × 1000 × 1000	1200 × 1200 × 1200
	Temperature Range (°C)	-49~+150	-	-70至+180	-49~+150	-49~+150
	Humidity Range (%RH)	20~98	-	20 至 98	20~98	20~98
Number		1	1	1	1	1

	① Salt spray chamber		② Dust chamber		③ Temperature and Humidity Chamber
Model	SC-1000/15-60	Model	ST 1000-U	Model	C-1500/39
image		image		image	
Test space dimensions W x D x H (mm)	1100 x 1000 x 1350	Test space dimensions W x D x H (mm)	950 x 950 x 1000	Test space dimensions W x D x H (mm)	1100 x 1475 x 949
Salt spraying	3.0±1ml/h/80cm ² h	Dust capacity (According to EN60529)	Dried talcum powder 2.5kg	Test space volume (ℓ)	1540
Maximum temperature for salt spray test (°C)	50	Maximum Load (kg)	72	Temperature range (°C)	-40 to 180
Temperature range (°C) (no humidity control)	-15 to 60			Temperature change rate heating (K/min) (According to IEC 60068-3-5)	3.5
Maximum Load (kg)	100				

	④ Industrial oven		⑤ Thermal Shock Chamber
Model	LKS-4C	Model	TSA-503EL-W
image		image	
Test Space Volume (ℓ)	4050	Test space volume (ℓ)	600
Test space dimensions W x D x H (mm)	1800 x 1500 x 1500	Test space dimensions W x D x H (mm)	1200 x 750 x 669
Maximum temperature (°C)	300	Temperature range (°C)	-50 to 150
Maximum Load (kg)	300	Maximum Load (kg)	220